

# HITCHHIKER™ RAMP



The HITCHhiker ramp connects to the outside of the vehicle by simply attaching the adjustable hitch mount bracket to most vans and SUVs equipped with a rear hatch or side-hinged doors and outfitted with a 1.25" (Class 2) or 2" (Class 3) hitch receiver.

The spring-assisted design allows the ramp to unfold using minimal lifting strength and easily refolds into a compact unit for easy transport.

Features an applied, high-traction reflective surface for use in all weather conditions. Manufactured of welded aircraft-grade aluminum. Lighted license plate kit included.

Patent pending.




Folds into a compact unit



Locking latch assures a rattle-free ride



Spring assisted hinge

SPECIFICATIONS	HITCHHKR 8
Made of aluminum	•
Non-skid surface	•
Usable size	8' x 32"
Ramp lifting weight (lbs.) *	25
Ramp weight (lbs.) *	110
Folded size	49½" x 36" 
Weight capacity (lbs.)	800
For wheelchairs & scooters	•
Usage guidelines	Vehicles equipped with 1.25" or 2" hitch receiver and rear hatch or side-hinged doors



Extends to 8' length and features side rail safety reflectors

\* Weights are approximate and may vary. Consult your equipment's owner guide for proper degree of incline. Never exceed its recommendations.



Bariatric weight capacity = 800 lbs. or greater

 UPS Shippable